

PRODUCT DATA HA38

Product Uses

HA38 contains an acidic activator and is used as a low level on line disinfection process for domestic hot and cold water services, water storage tanks, calorifiers and cooling towers and other industrial process water systems.

HA38 is used to produce chlorine dioxide when mixed with HA37 so as to help in the removal of biofilms and maintain heat transfer surfaces free of microbial deposits.

Product Application and Uses

HA38 is mixed with HA37 so as to achieve the desired concentration of normally between 0.1 – 0.5 mg/litre of chlorine dioxide within a system.

When using HA38 in combination with HA37, where ever possible dosage should be controlled automatically.

HA38 can be injected directly from the drum or from a dosing tank and is compatible with other products to form part of a water treatment programme for cooling systems to comply with the HSC Approved Code of Practice & Guidance – The control of legionella bacteria in water systems.

General Specification

Colour:	Colourless	pH:	1 – 2
Odour:	Odourless	Form:	Liquid
S.G. at 20°C:	1.06 – 1.09		

Packaging, Storage & Handling

HA38 is delivered in 25 litre or 205 litre drums and should be stored in a dry area.

Avoid storing HA38 with bases and in areas susceptible to frost and excessive heat.

HA38 is not classified as hazardous, however, we advise to avoid contact by wearing protective clothing, gloves and eye goggles in accordance with the relevant BS EN standards.

HA38/psi/17/08/05