

PRODUCT DATA

HA24

Product Uses

HA24 has been designed to prevent scale and corrosion in closed heating and chilled water systems containing ferrous and yellow metals.

A synergistic blend of inhibitors within HA24 is used to create a chemical film on all metal surfaces to prevent corrosion and chemically reacts with hardness salts to inhibit scale formation.

HA24 should **NOT** be used in systems that contain **ALUMINIUM**.

Product Application and Uses

HA24 can be added via a dosing pot or via a dosing pump for all closed systems. A passivation dose of HA24 should always be used after a system has been drained or after a system has been pre-commission or chemically cleaned.

HA24 can be injected directly from the drum or from a dosing tank and is compatible with other products such as glycol to form part of a water treatment programme for closed systems.

The use of our HA33 biocide is strongly recommended in systems dosed with HA24, so as to enhance the efficacy of HA24 in the presence of some types of bacteria.

General Specification

Colour:	Colourless	pH:	10 - 12
Odour:	Odourless	Form:	Liquid
S.G. at 20°C:	1.18 - 1.22		

Packaging, Storage & Handling

HA24 is delivered in 25 kg or 250 kg drums and should be stored in a dry area.

Avoid storing HA24 in areas susceptible to frost or excessive heat.

HA24 is classified as toxic and oxidising, so avoid contact by wearing suitable protective clothing, gloves and eye goggles in accordance with the relevant BS EN standards.

HA24/pdi/18/02/15