

PRODUCT DATA

HA57

Product Uses

HA57 has been designed primarily to prevent scale and corrosion in closed heating and chilled water systems containing aluminium, ferrous and yellow metals, but also finds uses within other metal working fluid systems.

A synergistic blend of buffers, alcoholamine – phosphate esters and yellow metal inhibitors have been formulated as a balanced blend of chemicals to perform several functions and is proven over a wide range of plant conditions.

HA57 can be easily monitored by way of on-site test kits.

Product Application and Uses

HA57 can be added via a dosing pot or via a dosing pump for all systems.

A passivation dose of HA57 should always be used after a system has been drained or after a system has been pre-commission or chemically cleaned.

HA57 can be injected directly from the drum or from a dosing tank and is compatible with other products such as glycol to form part of a water treatment programme for closed systems.

General Specification

Colour:	Pale yellow	pH:	7 - 8
Odour:	Perceptible odour	Form:	Liquid
S.G. at 20°C:	1.182		

Packaging, Storage & Handling

HA57 is delivered in 25 litre drums and should be stored in a dry area.

Avoid storing HA57 in areas susceptible to frost or excessive heat.

HA57 is classified as an irritant, so avoid contact by wearing suitable protective clothing, gloves and eye goggles in accordance with the relevant BS EN standards.

HA57/pdi/18/02/15