

PRODUCT DATA HA60

Product Uses

HA60 is a concentration of bacteria, bio-surfactants and enzymes for the digestion of fats, grease and organic waste products.

HA60 is active over a broad pH range and has been shown to be effective against most fats, grease and organic wastes.

Product Application and Uses

HA60 is normally shot dosed at regular intervals to the system. The quantity of HA60 required will vary according to concentration of fats, grease and the level of organic wastes. The volume of HA60 required would normally be calculated upon the waste pit volume and the retention time.

HA60 can be injected directly from the drum or from a dosing tank using a dosing pump or shot dosed directly into the waste pit.

Wherever possible, HA60 should be dosed automatically.

HA60 is biodegradable and requires no special discharge requirements.

General Specification

Colour:	Pale blue	pH:	6.0 – 7.0
Odour:	Barely perceptible odour	Form:	Liquid
S.G. at 20°C:	1.00 – 1.04		

Packaging, Storage & Handling

HA60 is delivered in 5 litre, 25 litre or 200 litre drums and should be stored in a dry area.

Avoid storing HA60 in areas susceptible to frost and excessive heat.

HA60 is classified as non-hazardous, but contact should be avoided by wearing suitable protective clothing, gloves and eye goggles in accordance with the relevant BS EN standards.

HA60/pdi/13/07/04